			PATRI	OT G25			
	1 Model						FY25D
	2	Power Type					LPG
1	3	Rated Capacity at 3000mm lift height			lbs	5513	
1	4	True Capacity at		118 in	lift height	lbs	5513
General	5		Load Centre			inch	20
	6	* Lift Height			3 stage mast	inch	118
	7	* Fork Size		L×W	/×T	inch	42 x4.7x1.57
	8	Mast Tilt Angle		F/R		Deg	6°/12°
	9	Front Overhang (Wheel center to fork face)			inch	19	
	10	Ground Clearance (Bottom of mast			inch	5	
	11	Overall Dimension		Length to face of fork(Without fork)		inch	94
	12			Overall Width		inch	45
	13			Mast Lowered Height		inch	81
	14			Mast Extended Height (with backrest)		inch	159
	15			Overhead Guard Height		inch	81
Characteristic	16		Turning Radius (outside)			inch	91
&Dimension	17		Min. insecting aisle			inch	94
	18	Speed		Travel (En	mpty load)	mph	11.8
	19		L		Lifting(Full load)		20.8
Performance	20	Max.Gradeability			%	20	
	21	* Tire		Front x 2	Air Pneumatic		7.00-12-12
	22			Rear x 2			6.00-9-10
	23	Wheelbase			inch	63	
Chassis	24	Service weight			lbs	8159	
	25	Battery	Voltage/Capacity			V/Ah	12/80
	26	* Engine					
	27						
	28 Rated output/r.p.m.			HP	56/2700		
	29		Rated torque/r.p.m.			N·m	185/1350
	30		No.of Cylinder				4
	31 Bore×Stroke				mm	3.5x3.9	
	32		Displacement Fuel Tank Capacity * Transmission Type			cc	2448
	33					gal	15.85
	34	* Transmission					Hydraulic
Power&Trans	35		Stage FWD/RVS				1/1
mission	36	Operating Pressure for attachment				Mpa	17.5