			PATRIC	<b>DT FB20</b>			
	1	Model					FB20
	2 Power Type						Electric
	3	Rated Capacity at 3000mm lift height				lb	4500
	4		True Capacity at <b>118 mm</b> lift height			lb	4500
General	5		1 1	Centre	- C	in	20
	6	* Lift Height			2 stage mast	in	118
	7	* For	k Size	L×W×T		in	<b>42</b> x4.7x1.6
	8	Mast Ti	lt Angle	F/R		Deg	6°/12°
	9	Front Overhang (Wheel center to fork face)				in	18.3
	10	Tre	ead	F/R		in	37.8/37.4
	11	Ground Clearance (Bottom of			ıst)	in	4.3
	12	Fork	Space	Min. / Ma×.		in	9.4/40.9
	13			Length to face of fork(Without fork)		in	93
	14	-		Overall Width		in	45.7
	15			Mast Lowered Height		in	80.9
	16			Mast Extended Height (with / without backrest)		in	156
	17	Overall D	imension	Overhead Guard Height		in	88.2
	18	Turning Radius (outside)			in	81.7	
cteristic&Dime	19	Min. insecting aisle			in	88.6	
	20			Travel (Empty load)		mph	8.7
	21	Speed		Lifting(Full load)		in	11.8
Performance	22	Max.Gradeability			%	15	
	23	* Tire		Front x 2	Air Pneumatic		7.00-12-12
	24			Rear x 2			18x7-8-14
	25	Wheelbase			in	59.4	
Chassis	26		Service weight			lh	9383
	30			Drive		hp	14.75
	31	Motor		Lift		hp	11.53
		Battery	Battery Voltage/Capacity			V/Ah	48/560
		* Controller				AC	
wer&Transmissi	32	(	Operating Pressure for attachment			Mpa	18
	52			es / Attachments		ιτιρα	-