			PATRIC	OT FB25			
	1	Model					FB25
	2	Power Type				Electric	
	3	Rated Capacity at 3000mm lift height			kg	5513	
	4	7	True Capacity at	118 in	lift height	kg	5513
General	5	Load Centre				mm	19.7
	6		* Lift Height		2 stage mast	mm	118
	7	* For	k Size	L×V	V×T	mm	42 x4.7x1.57
	8	Mast Ti	lt Angle	F/R		Deg	6°/12°
	9	Front Overhang (Wheel center to fork face)				mm	18.3
	10	Tre	ead	F/R		mm	37.8/37.4
	11	Ground Clearance (Bottom of mast)			st)	mm	4.3
	12	Fork	Space	Min. / Ma×.		mm	9.4/41
				Length to face of fork(Without			
	13 fork)			mm	92.9		
	14			Overall Width		mm	45.7
	15			Mast Lowered Height		mm	80.9
	1.6	Mast Extended Height (with /					155.0
	16		without backrest)		mm	155.9	
	17	Overall Dimension		Overhead Guard Height		mm	88.2
	18	Turning Radius (outside)				mm	81.7
cteristic&Dime	19	Min. insecting aisle			mm	88.6	
	20			Travel (Empty load)		moh	8.7
	21	Speed		Lifting(Full load)		mm/s	10.6
Performance	22		Max.Gra	adeability		%	15
Chassis	23			Front x 2	Air	mm	7.00-12-12
	24	* Tire		Rear x 2	Pneumatic	mm	18x7-8-14
	25	Wheelbase				mm	59.4
	26		Service	e weight		kg	#REF!
	30			Drive		kw	11
	31	Motor		Lift		kw	8.6
		Battery Voltage/Capacity		V/Ah	48/630		
		4			T.		1.6
		* Controller Type				3.5	AC
wer&Transmissi	32	Operating Pressure for attachment				Mpa	18
		es / Attachments	3		-		