





General Specs

Model FD70G

Power Type Diesel

Engine KOHLER KDI1903TCR

Transmission Hydraulic

Fuel System Diesel

Chassis Type Air Pneumatic

Paint -


Rated Capacity at 15500 3000 mm Lift Height (*lbs*)

True Capacity at **requested** 12100 Lift Height (*lbs*)

Load Center (inch) 24








Model	FD70G
Lift Height - 3 Stage Mast (inch)	177
Fork Size - $L \times W \times T$ (mm)	96 × 5.9 × 2.75
Mast Tilt Angle - F/R (Deg)	6°/6°
Front Overhang Wheel Center to Fork Face (inch)	23.4
Ground Clearance Bottom of Mast (inch)	7.9
Overall Dimension	
Length To Face Of Fork Without Fork (Inch)	140
Overall Width (Inch)	79
Mast Lowered Height (Inch)	106
Mast Extended Height With Backrest (Inch)	232
Overhead Guard Height (Inch)	96
Turning Radius - Outside (Inch)	132
Min. Insecting Aisle (Inch)	120

Chassis

Model FD70G Tire - Front x 4 8.25 - 15 - 14 Air Pneumatic 8.25 - 15 - 14 Rear x 2 8.25 - 15 - 14 Air Pneumatic 88.6 Service Weight (lbs) 22500

Performance

Model	FD70G
Speed - Travel (Empty Load) (mph)	18.6
Lifting (Full Load) (in/s)	18
Max. Gradeability (%)	20







Power and Transmission

Model	FD70G
Battery - Voltage/Capacity (V/Ah)	(12/80) x 2
Engine	
Rated Output / r.p.m (kw)	89/2200
Rated Torque / r.p.m (N.m)	488/1600
No. of Cylinder	4
Bore x Stroke (mm)	102 x 115
Displacement (cc)	3800
Fuel Tank Capacity (L)	125
Transmission - Type	Hydraulic
Stage - FWD/RVS	2/2
Accessories / Attachments	Cab with Heat 96" Side Shift

